




dimensioni in mm
dimensions shown in mm




C63




ruolo - tube



G39



GAF39



FG42

CARATTERISTICHE:

Tipo di applicazione: verticale

Ambiente di applicazione: interno

Cassonetto: C63 in alluminio estruso composto da una parte fissa e una parte mobile ispezionabile. Coppie di testate laterali in PVC bianche o nere, autoportanti in guida

Rullo di avvolgimento: Ø 30 mm in alluminio estruso con ogiva

Guide: G39/GAF39 in alluminio estruso con duplice funzione di trattenere il tessuto tramite bottoni di plastica e di chiudere gli spazi laterali onde evitare le lame di luce nel caso in cui la tenda abbia funzione oscurante

Fondale: FG42 piatto in alluminio estruso con tappi scorrevoli in PVC

Manovra: a molla Ø 30 mm con filo armonico C98, senza arresto

Fissaggio: frontale o laterale delle guide; fissaggio a soffitto del cassonetto opzionale.

CHARACTERISTICS:

Application: vertical

Installation: indoors

Headbox: C63 extruded aluminum headbox with removable cover and black/white plastic end cheeks that permit the box to be fitted directly to the side channels

Roller tube: Ø 30 mm extruded aluminum tube with slot

Side channels: G39/GAF39 extruded aluminium side channels to withhold the fabric (plastic studs run inside the rail) and close the lateral gaps (hence reducing light infiltration: important for blackout system)

Hem bar: FG42 extruded aluminum flat hem bar with PVC caps

Operation: C98 harmonic spring operation without endstop

Mounting: wall or mounting in recess; optional ceiling mounting.

colori standard - *standard colours*

bianco Ral 9010 - *white Ral 9010*

nero Ral 9005 opaco - *matt black Ral 9005*

argento anodizzato - *silver anodised*

tessuti abbinabili - *suitable fabrics*

per l'utilizzo dei tessuti consultare la sezione dei teli confezionati e/o Tabella "A"

for fabric choice consult the fabric section and Tab. "A"

supplementi - *supplement*

